



Premium PET Strapping

PET Strapping is the polyester strap you can rely on to bind right and stay strong. Tougher than polypropylene and more economical than steel strapping, it keeps integrity and retains tension for ideal load stability. It's tough (even penetration by errant nails won't stop it), it's safe and it's easy to apply – there are no sharp edges and it can be used by hand or with automated machinery.



Product Options

Code	Description	Rolls/pallet
42005	Premium PET Strapping 9mm x 0.65mm x 3200m, Embossed surface Breaking strain: 210kg	20
42018	Premium PET Strapping Fully Auto Grade 12mm x 0.7mm x 2200m, Embossed surface Breaking strain: 300kg	24
42017	Premium PET Strapping 16mm x 1.0mm x 1150m, Smooth surface Breaking strain: 620kg	24

PET Strapping Dispenser

Keep your pallet PET Strapping in reach and at hand with this fast, easy and efficient dispenser. While lightweight in design it has stay-tough construction, ensuring long-term strapping peace of mind.



Product Options

Code	Description
42003	PET Strapping Dispenser Strong, lightweight, easy to use with wheels, handle and tool storage.

To find out more get in touch today at:
info@universalpackaging.co.nz or on 0800 700 000
universalpackaging.co.nz





The OrgaPack range of strapping equipment is well respected internationally for some very good reasons. Firstly, there's the well-balanced design, ensuring day after day of stress-free use. Then there's the functionality.

Users have strap alignment measurements, favourite strapping mode, real time indication of applied tension force and variable tension speed control – all within easy reach and at the touch of a finger.



OR-T 130



Lightweight ease: Fast, easy and effortless, the OR-T 130 provides lightweight binding capability for functional pallet strapping.

OR-T 260



Everyday reliability: With proven performance and ideal hand-held balance, the durable design and practical functionality of the OR-T 260 makes it the most popular strapping tool around the world.

OR-T 450



Heavy-duty strength: Delivering an incredible 400-4500N of tension force the OR-T 450 is at the top of game for hand-held-in-control strapping capability.

	OR-T 130 Light	OR-T 260 Universal	OR-T 450 Heavy
Product Codes	29419	29417	29418
Strap type	PET + PP	PET + PP	PET + PP
Strap width	9 - 13 mm	13 - 16 mm	16 - 19 mm
Strap thickness	PET: 0.4 - 0.8 mm; PP: 0.5 - 0.8 mm	0.5 - 1.0 mm	0.8 - 1.3 mm
Weight	3.6 kg	3.8 kg	4.3 kg
Tension force	150 - 1200 N	400 - 2500 N	400 - 4500 N
Variable Tension Speed	0 - 290 mm/s	0 - 220 mm/s	0 - 120 mm/s
Cycles / Charge	up to 800	up to 800	up to 800
Battery	Bosch Li-Ion 18V, 2.0Ah	Bosch Li-Ion 18V, 2.0Ah	Bosch Li-Ion 18V, 4.0Ah
Charging time battery	15 - 30 min	15 - 30 min	25 - 35 min
Motor technology	Single motor technology, brushless	Single motor technology, brushless	Single motor technology, brushless
Dimension (L x W x H)	370 x 141 x 135 mm	370 x 141 x 135 mm	370 x 143 x 135 mm

To find out more get in touch today at:
 info@universalpackaging.co.nz or on 0800 700 000
universalpackaging.co.nz

